

MC120 Classic Red



Engine

McCormick BetaPower 6 cyl Turbo Diesel
TIER 3 6TA 6.728 litres
Waste-gate turbo/Intercooler
Dry Dual Element Air Cleaner
118 HP @ 2200 rpm
Torque 515 Nm
Torque Rise 40% @ 1250 rpm
Fully tilting hood

World Proven Transmission

16 Forward Speeds / 12 Reverse Speeds
4 Ranges with 4 Powershifts in each Range
Power Shuttle with neutral
Soft shift facility in 4th range
Transmission clutches are oil cooled and pressure lubricated
Multi-plate differential lock for fool-proof operation
40km/h Roadspeed
Electronic 4WD engagement
4WD/Diff Lock features auto function

PTO

Independent, wet multi-plate clutch
Electronically modulated system
PTO Speeds 540/1000
Dry change 6/21 spline reversible shaft
105- PTO Hp (mfe)

Hydraulics

Full electronic lift control system c/w ride control
Hi-Flo Load Sensing Closed Centre Hydraulics
109 l/min total flow
2 Standard spool valves S/D acting
Low Pressure return line kit
Power beyond & flow control std
3 point linkage, category II ball ends
5871 lift capacity
Swinging Draw Bar
Front Weight Bracket

Axles & Steering

55 degree turning angle
Tilting, Telescopic Steering Wheel
Reduced steering revolutions
Centre drive with limited slip diff
Flanged Axle

Operator Environment

Industry leading 72dB(A) cab
Digital Dash
Air Conditioning
Front and rear window wipers
External mirrors
Deluxe seat
Hydrostatic steering
Radio Ready prewired with two speakers
7 Worklights
Rotating Beacon
Tool box

Standard Tyres

Front 420/70R28
Rear 520/70R38

Weights and Dimensions

Length with weights	4811 mm
Overall Height	2810 mm
Wheelbase 4WD	2650 mm
Standard Weight	5750 kg
Fuel Capacity	265 Litres

Warranty

2 years or 2400 hours from Installation